

# HEAVY DUTY TILLER



**Features:**

- Operates with tractor hydraulics and three point linkage.
- Simple, rugged frame design ensures strength and rigidity.
- Tines are spring-loaded to prevent damage when working in stony ground or root obstructed soil.
- Fitted with reversible shovel points.

**Utilities:**

- Multipurpose tillage implement for stubble mulching, weeding and general cultivation.
- For preparing seed beds economically and quickly in a variety of soil and crop conditions.
- Ideal implement for loosening and aerating soil.

**Specifications:**

Parameters	TIPS 1206 Heavy Duty Tiller 9 Tine	TIPS 1212 Heavy Duty Tiller 11 Tine	TIPS 1203 Heavy Duty Tiller 13 Tine
Overall Height	1080 mm	1090 mm	1225 mm
Overall Width	2000 mm	2515 mm	2970 mm
Overall Length	880 mm	865 mm	865 mm
Under beam clearance	550 mm	550 mm	550 mm
Weight	248 Kgs	300 Kgs	365 Kgs
Linkage Type	CAT I – 3 Point Linkage	CAT II – 3 Point Linkage	CAT II – 3 Point Linkage
Type	Fixed	Fixed	Fixed
Power Requirement	30 HP & Above	45 HP & Above	60 HP & Above

\* The weight and working data contained in the present leaflet are supplied for information only and are not binding. Specification and size can be altered as part of ongoing product modification / improvement