



MOULD BOARD PLOUGH

TIPS 2151 / 2152



Features:

- Wide under beam clearance
- Long Land slide provides stability to the implement
- Available in 2,3 and 4 Furrow versions
- Plough easily through hard abrasive soil under low moisture level
- Using suitable conversions kits 2 and 3 Furrow versions can be converted to a 3 and 4 Furrow versions, respectively
- Bar point bottoms ensure longer life as they can be extended or reversed and reused till the last possible length

Utilities:

- Cuts heavy trash and buries it completely, especially in sugarcane and cotton fields
- Under ideal conditions, this equipment provides excellent soil inversion

Specifications:

Product Code	TIPS2151	TIPS2152
Size	2 Furrow	3 Furrow
Frame	65x65x8mm Box & 50mm Round	65x65x8mm Box & 50mm Round
Tyne	36mm profile cut single piece	36mm profile cut single piece
Length (L)	1300mm	1880mm
Width (N)	738mm	738mm
Height	1066mm	1066mm
Blade	10mm	10mm
Mould board	8mm	8mm
Shovel	40x25mm Bar (EN42 Forged)	40x25mm Bar (EN42 Forged)
3 Point linkage	65x16mm Flat & 31mm Square	65x16mm Flat & 31mm Square
Clamp	125x50mm	125x50mm
Width of Cut (B)	610mm (max)	910mm(max)
Depth of Cut	350mm (max)	350mm (max)
Weight	235kgs (approx.)	350 Kgs. (approx.)
Power Required (HP)	30-40	55-60

* The weight and working data contained in the present leaflet are supplied for information only and are not binding. Specification and size can be altered as part of ongoing product modification / improvement



Tractors and Farm Equipment Limited

(A Member of the Amalgamations Group)

IMPLEMENTS DIVISION

Huzur gardens, Sembiam, Chennai - 600 011- India

Phone: 044- 2558 2840, Fax: 044- 2558 2839