

TIPPING/NON TIPPING TRAILER



Features:

- Robust all steel welded construction.
- Tipping through finger tip tractor hydraulics control.
- Tipping model gives clean and rapid discharge of load at 45° to 50°.
- Can be hitched and unhitched from the Driver's seat.
- Effective Parking brake is provided.
- Available with tyre size 7.50 x 16 and 9.00 x 16 and with 14" and 20" side boards.
- Axle location ensures constant load transfer to the tractor for effective traction.

Utilities:

- Low loading height facilitate loading of any type of material.
- Tipping arrangement facilitates quicker discharge of material.
- Highly useful for the transportation of agricultural produce, fertilizer etc.,

Specifications:

Platform size (mm)	3050
Overall length inclusive of tow bar(mm)	4050/4100
Overall width (mm)	1920
Door Size (mm)	355/510
Capacity (in Cu. m)	2.5 / 3.00
Loading Height (mm)	880/938
Suspension	Rigid
Wheel Track (mm)	1510/1520
Clearance beneath axle (mm)	350/400
Tyre size	7.50 x 16 –12 PR / 9.00 x 16 – 16 PR

* The weight and working data contained in the present leaflet are supplied for information only and are not binding. Specification and size can be altered as part of ongoing product modification / improvement